Zero Fridge Freezer Range Features & Benefits

- Dual, independently controlled cooling zones (dual zone models only)
- Each zone can be set to fridge, freeze or off
- Removable compartment divider and internal lid (69L dual zone only)
- Integrated wireless monitoring & control via compatible Bluetooth enabled devices (LINX, Android & IOS)
- Boost function for rapid cool down
- Anti-condensation technology
- Highly efficient, variable-speed compressor
- Convenient USB 5V, 3000mA outlet for charging phones and alike (fridge must be connected to DC or AC power source for charging)
- Dual DC power inlet at opposing ends for customised installations
- Front AC power inlet for quick home or powered site connection
- Tough, durable steel outer casing
- Full height corner mouldings for added protection
- Recessed carry handles with integrated tie down points
- Quick release, front opening lid with non-slip glass/bottle provision (44L only)
- Quick release, reversible, side opening lid/s with non-slip glass/bottle provision (60L, 69LDZ &96LDZ)
- Easy-view LED display
- Low power draw LED interior light/s
- Versatile, removable internal basket system with provision for tall items/bottles















Specifications

<u>Capacity – Zero 44L</u> 44L Single Zone

65 x 375ml cans **Cooling Capacity** -22°C to +10°C

Weight 21.6kg

External Dimensions

(mm): (L) 675 (W) 423 (H) 496

Internal Dimensions

Upper Compartment (mm): (L) 482 (W) 292 (H) 203 Lower Compartment (mm): (L) 316 (W) 292 (H) 180

Power

Voltage: 12/24V DC / 100-240V AC Integrated battery protection system

Consumption: 0.8Ah*

* DC12V set at 5°C, 32°C ambient temperature

Removable upper basket with built-in folding access door



























<u>Capacity – Zero 60L</u> 60L Single Zone

96 x 375ml cans Cooling Capacity -22°C to +10°C

Weight 24.6kg

External Dimensions (mm): (L)755 (W) 469 (H) 496

Internal Dimensions Upper Compartment

(mm): (L) 580 (W) 326 (H) 197

Lower Compartment

(mm): (L) 402 (W) 326 (H) 180

Power


Voltage: 12/24V DC / 100-240V AC Integrated battery protection system

Consumption: 0.8Ah*

* DC12V set at 5°C, 32°C ambient temperature































Capacity - Zero 69LDZ

69L Dual Zone (24L/45L)

87 x 375ml cans with divider, 108 without

Cooling Capacity -22°C to +10°C

Weight 28.3kg

External Dimensions

(mm): (L)755 (W) 469 (H) 564

Internal Dimensions

Front Zone

Upper Compartment

(mm): (L) 380 (W) 326 (H) 264

Lower Compartment

(mm): (L) 202 (W) 326 (H) 180

Rear Zone

(mm): (L) 170 (W) 326 (H) 444

Power

Voltage: 12/24V DC / 100-240V AC Integrated battery protection system

Consumption: 2.9Ah*

* DC12V set at -15°C zone 1, 3°C zone 2, 32°C ambient

temperature



Removable









basket with built-

in folding access







Capacity - Zero 96LDZ

96L Dual Zone (41L/55L) 144 x 375ml cans Cooling Capacity -22°C to +10°C

Weight 32.9kg

External Dimensions

(mm): (L) 935 (W) 548 (H) 509

Internal Dimensions

Front Zone

Upper Compartment

(mm): (L) 354 (W) 403 (H) 209

Lower Compartment

(mm): (L) 176 (W) 403 (H) 180

Rear Zone

(mm): (L) 354 (W) 403 (H) 389

Power

Voltage: 12/24V DC / 100-240V AC Integrated battery protection system

Consumption: 3.1Ah*

















Wireless Monitor & Control

- Monitor and control your Zero Fridge/Freezer on LINX* or a compatible Bluetooth enabled device
- Displays:
- Target and cabinet temperatures (multi-zone for dual zone models),
- Compressor status (run, boost, idle & standby)
- Battery voltage
- Mode setting (up to 3 different user defined modes)
- Fridge name (user defined)
- **Controls:**
- Turn on/off
- Fridge temperature (either by selecting pre-defined user mode/s or manually setting temperature)
- Alter Settings:
- Disconnect fridge from Bluetooth communication
- Rename Fridge
- Normal or Boost mode
- Temperature unit C° or F°
- Battery protection mode (high, medium or low)
- Customise user mode settings
- Add multiple fridges
- Delete fridge

^{*}Compatible with LINX.















