

SANTANA							
Vehicle/Model	Axle Loc'n	Year	Description	Shaft Diameter	Shaft Spline	Ratio	ARB Part No.
Anibal, PS10	Front		All models (Land Rover type)		10	All	RD127 <sup>1</sup>
	Rear		All models		24	All	RD126
PS300	Front		10 bolt RG (Suzuki Vitara type)	27.4 (1.08")	26	All	RD208
	Rear		12 bolt RG	27.4 (1.08")	26	All	NA <sup>2</sup>
PS350	Front		10 bolt RG (Suzuki Vitara type)	27.4 (1.08")	26	All	RD208 <sup>2</sup>
	Rear		12 bolt RG	27.4 (1.08")	26	All	NA <sup>2</sup>

<sup>1</sup> Requires ring gear spacer (ARB part # RD03A) ordered separately.

<sup>2</sup> Requires 10 bolt RD208 conversion using PS300 front third member assembly of same ratio.

SSANGYONG							
Vehicle/Model	Axle Loc'n	Year	Description	Shaft Diameter	Shaft Spline	Ratio	ARB Part No.
Musso / Rexton / Korando	Rear	1996 on	Dana 44, manual	33.3 (1.31")	30	4.55	●●RD116 <sup>1</sup>
		1996 on	Dana 44, automatic	33.3 (1.31")	30	3.73	●●RD117 <sup>1</sup>

●● ARB Diff Cover available (RED and/or BLACK).

<sup>1</sup> See performance section of this guide for non-standard upgrade model(s) available for this application.

SUZUKI							
Vehicle/Model	Axle Loc'n	Year	Description	Shaft Diameter	Shaft Spline	Ratio	ARB Part No.
Sierra / Samurai / Jimny Holden Drover Maranti Gypsy	Front	2003 on	Jimny model with 10 bolt RG	23.9 (0.94")	22	All	RD206
		1998-03	Jimny model with 8 bolt RG	23.9 (0.94")	22	All	RD207 <sup>4</sup>
		1984-98	Leaf spring suspension	23.9 (0.94")	22	All	RD205
	Rear	1984 on	1.3 litre models only	27.4 (1.08")	26	All	RD208
Jimny (Japan only) (JA11, JA12)	Front	1990-95	JA11, 660cc turbocharged engines ONLY	23.9 (0.94")	22	All	RD207 <sup>4</sup>
	Rear	1990-98	JA11 & JA12, 660cc turbocharged engines	27.4 (1.08")	26	All	RD208
Vitara / Sidekick Grand Vitara, XL7	Front	1988-98	26 spline	27.4 (1.08")	26	All	RD208
			22 spline	23.9 (0.94")	22	All	RD205
		1998-05	26 spline ADD	27.4 (1.08")	26	All	NA <sup>2</sup>
		2005 on				All	NA
	Rear	1988-93	Suzuki 10 bolt RG	27.4 (1.08")	26	All	RD204 <sup>1</sup>
		1993-00	Suzuki 12 bolt RG (excl. Grand Vitara)	27.4 (1.08")	26	All	RD209 <sup>1</sup>
1998-05		26 spline	27.4 (1.08")	26	All	NA <sup>3</sup>	
	2005 on	28 spline IRS	28.8 (1.13")	28	All	NA	

<sup>1</sup> Note that in some (Asian) countries, the Dana 30 salisbury type axle was used from 1993 on. See RD100 & RD101.

<sup>2</sup> Grand Vitara/XL7 (to 2005) front requires conversion using RD208, Vitara/Sidekick third member assembly and free wheeling hubs.

<sup>3</sup> Grand Vitara/XL7 (to 2005) rear requires conversion using Vitara/Sidekick third member assembly (& 26 spl axle shafts if required). No application for current model (2005 on) Grand Vitara.

<sup>4</sup> See performance section of this guide for non-standard upgrade model(s) available for this application.